

ENTECH

Environmental Technology Limited
Entech House, London Road, Woolmer Green
Knebworth, Hertfordshire, England SG3 6JR
Telephone: 01438 812812 Fax: 01438 814224
E-Mail Address: admin@etl-entech.co.uk

PRODUCT SPECIFICATION (REV.03)

JUNE 2008

ENTECH SERIES 1459 MINL.CMS, consisting of press-formed profiled facing panels, from 1.6mm zinc coated mild steel, with a central flat panel and two outer panels with flap sections curving to return vertically, all visible external surfaces of the panels being finished in Entech High Quality LU Compliant Polyester Powdercoat RAL 9016X White 30 % gloss, or alternative compliant finish as specified, the outer panels being fixed with continuous stainless steel hinges to a support framework, the support framework being fabricated from hot dipped galvanised mild steel channel sections (Unistrut or similar), cut and welded and protected with zinc-rich paint, the panels being secured in the closed position with ¼-turn fasteners and incorporating a detachable mechanical restraining strut, or a safety wire to prevent the outer panel falling to the full-open position, the support frames being fixed to the tunnel substrate with M8 resin anchors @ 750mm nominal centres, the panels being to a nominal length of 900mm grouped in an assembly of 3 panels, overall nominal length 2700mm, with provision in the central fixed flat panel for a lipped press-formed cut-out for a lighting unit 1631mm length, or being in single 900mm units with a lighting unit 720mm length, (lighting units supplied and installed by others), all being to detailed design and approval.